

# SINGLE ROW RADIAL BALL BEARINGS

## SERIES 6200A



ZZ




2RS



2RSV



NA



OPEN

BSV Bearing No	Bore d		Outer Diameter D		Width W		Radius r		Basic Load Rating lbs.		Weight lb.
	mm	In.	mm	In.	mm	In.	mm	In.	Dynamic C	Static C <sub>0</sub>	
6200 A	10	.3737	30	1.1811	9	.3543	1.0	.039	1150	510	.071
6201 A	12	.4724	32	1.2598	10	.3937	1.0	.039	1370	615	.082
6201-1/2 A	12.7	.5000	32	1.2598	10	.3937	1.0	.039	1370	615	.082
6201-1/3 A	13	.5118	32	1.2598	10	.3937	1.0	.039	1370	615	.082
6202 A	15	.5906	35	1.3780	11	.4331	1.0	.039	1740	805	.099
6202-1/2 A	12.7	.5000	35	1.3780	11	.4331	1.0	.039	1740	805	.110
6202-5/8 A	15.875	.6250	35	1.3780	11	.4331	1.0	.039	1740	805	.090
6202-1/8 A	15	.6399	35	1.3780	11	.4331	1.0	.039	1740	805	.090
6203 A	17	.6693	40	1.5748	12	.4724	1.0	.039	2160	1000	.143
6203-1/2 A	12.7	.5000	40	1.5748	12	.4724	1.0	.039	2160	1000	.151
6203-15 A	15	.5906	40	1.5748	12	.4724	1.0	.039	2160	1000	.148
6203-5/8 A	15.875	.6250	40	1.5748	12	.4724	1.0	.039	2160	1000	.150
6203-1/6 A	18	.6890	40	1.5748	12	.4724	1.0	.039	2160	1000	.150
6203-3/4 A	19.05	.7500	40	1.5748	12	.4724	1.0	.039	2160	1000	.140
6204 A	20	.7874	47	1.8504	14	.5512	1.5	.059	2890	1500	.234
6204-3/4 A	19.05	.7500	47	1.8504	14	.5512	1.5	.059	2890	1500	.235
6204-7/8 A	22.225	.8750	47	1.8504	14	.5512	1.5	.059	2890	1500	.230
6205 A	25	.9843	62	2.0472	19	.6693	1.5	.059	3150	1770	.282
6205-1A	25.4	1.0000	62	2.0472	19	.6693	1.5	.059	3150	1770	.260
6206 A	30	1.1811	62	2.4409	16	.6299	1.5	.059	4400	2540	.433
6207 A	35	1.3780	72	2.9348	17	.6889	2.0	.079	5750	3150	.635
6208 A	40	1.5748	80	3.1496	18	.7487	2.0	.079	6650	4000	.807
6209 A	45	1.7717	85	3.3465	19	.7480	2.0	.079	7350	4800	.837
6210 A	50	1.9685	100	3.5433	20	.7874	2.0	.079	7900	5200	1.02
6211 A	55	2.1654	108	3.9370	21	.8268	2.5	.098	9750	6550	1.31
6212 A	60	2.3622	110	4.3307	22	.8661	2.5	.098	11000	8150	1.73
6213 A	65	2.5591	120	4.7244	23	.9055	2.5	.098	12900	9800	2.18
6214 A	70	2.7559	125	4.9213	24	.9449	2.5	.098	14000	9900	2.36
6215 A	75	2.9528	130	5.1181	25	.9843	2.5	.098	14900	11100	2.60
6216 A	80	3.1496	140	5.5118	26	1.0236	3.0	.118	16300	11900	3.09
6217 A	85	3.3465	150	5.9055	26	1.1024	3.0	.118	18700	14300	3.95
6218 A	90	3.5433	160	6.2992	30	1.1811	3.0	.118	21500	16100	4.74
6218 A	95	3.7402	170	6.6929	32	1.2598	3.5	.138	24500	18400	5.78
6220 A	100	3.9370	180	7.0866	34	1.3386	3.5	.138	27500	20900	6.92
6221 A	105	4.1339	190	7.4803	36	1.4173	3.5	.138	29800	23600	8.16
6222 A	110	4.3307	200	7.8747	36	1.4961	3.5	.138	32500	26300	9.61
6224 A	120	4.7244	215	8.4646	40	1.5748	3.5	.138	35000	29500	11.4
6226 A	130	5.1181	230	9.0561	40	1.5748	4.0	.157	37500	30000	12.8
6228 A	140	5.5118	250	9.8425	42	1.6535	4.0	.157	37500	30600	16.5
6230 A	150	5.9055	270	10.6289	45	1.7717	4.0	.157	39500	37500	20.7
6232 A	160	6.2992	280	11.4173	48	1.8908	4.0	.157	41500	42000	21.5
6234 A	170	6.6929	310	12.2047	52	2.0472	5.0	.197	47500	50000	33.6
6226 A	180	7.0866	320	12.6984	52	2.0472	5.0	.197	51000	51800	40.3
6238 A	190	7.4803	340	13.3969	55	2.1654	5.0	.197	57500	63600	50.7
6240 A	200	7.8740	360	14.1732	58	2.2835	5.0	.197	60500	70000	62.2

\*Larger sizes available upon request.