



Shaft Dia. in. d	SST Bearing No.	Dimensions (in.) (mm)									Set Screw ds	Load Rating lb.		Weight										
		D	L	Bi	Be	n	m	k	H	G		Dynamic	Static	kg	lbs.									
1/2	SA201-8	1.5748	1.125	0.748	0.512	0.256	0.492	1.125	0.531	0.188	1/4-28	2150	1072	0.14	0.31									
5/8	202-10	40	28.6	19	13	6.5	12.5	28.6	13.5	4.8				0.13	0.29									
3/4	CSA104-12	1.6535	1.040	0.970	0.476	0.238	0.737	1.300	0.521	0.190	1/4-28	2320	1000	0.12	0.28									
		42	26.3	24.6	12	6	18.7	33	13	4.8				0.12	0.28									
3/4	SA204-12	1.8504	1.218	0.843	0.551	0.295	0.531	1.260	0.531	0.188	1/4-28	2880	1484	0.15	0.33									
		47	31	21.4	14	7.5	13.5	32	13.5	4.8				0.15	0.33									
7/8	SA205-14	2.0472	1.218	0.843	0.591	0.295	0.531	1.500	0.531	0.188	1/4-28	3152	1765	0.21	0.46									
15/16	205-15													52	31	21.4	15	7.5	13.5	38.1	13.5	4.8	0.19	0.42
1	205-16													52	31	21.4	15	7.5	13.5	38.1	13.5	4.8	0.18	0.40
1-1/16	SA206-17	2.4409	1.406	0.937	0.629	0.354	0.583	1.748	0.625	0.234	5/16-24	4375	2542	0.35	0.77									
1-1/8	206-18													62	35.7	23.8	16	9	14.8	44.4	15.9	6	0.33	0.73
1-3/16	206-19													62	35.7	23.8	16	9	14.8	44.4	15.9	6	0.31	0.68
1-1/4	206-20													62	35.7	23.8	16	9	14.8	44.4	15.9	6	0.29	0.64
1-1/4	SA207-20	2.8346	1.531	1.000	0.669	0.374	0.626	2.188	0.688	0.266	5/16-24	5777	3459	0.56	1.23									
1-5/16	207-21													72	38.9	25.4	17	9.5	15.9	55.6	17.5	6.8	0.53	1.17
1-3/8	207-22													72	38.9	25.4	17	9.5	15.9	55.6	17.5	6.8	0.51	1.12
1-7/16	207-23													72	38.9	25.4	17	9.5	15.9	55.6	17.5	6.8	0.48	1.06
1-1/2	SA208-24	3.1496	1.719	1.187	0.708	0.433	0.756	2.377	0.719	0.266	5/16-24	5787	4042	0.68	1.50									
1-9/16	208-25													80	43.7	30.1	18	11	19.2	60.3	18.3	6.8	0.65	1.43
1-5/8	SA209-26	3.3465	1.719	1.187	0.748	0.433	0.756	2.499	0.719	0.266	5/16-24	7357	4598	0.76	1.68									
1-11/16	209-27													85	43.7	30.1	19	11	19.2	63.5	18.3	6.8	0.73	1.61
1-3/4	209-28													85	43.7	30.1	19	11	19.2	63.5	18.3	6.8	0.69	1.52
1-7/8	SA210-30	2.5433	1.719	1.187	0.787	0.433	0.756	2.751	0.719	0.266	5/16-24	7895	5180	0.83	1.83									
1-15/16	210-31													90	43.7	30.1	20	11	19.2	69.8	18.3	6.8	0.79	1.74
2	SA211-32	3.9370	1.906	1.280	0.945	0.472	0.807	2.999	0.813	0.313	3/8-24	9757	6552	0.96	2.12									
2-1/8	SA211-34													100	48.4	32.5	24	12	20.5	76.2	20.6	8	0.87	1.92
2-3/16	211-35													100	48.4	32.5	24	12	20.5	76.2	20.6	8	0.81	1.79
2-1/4	SA212-36	4.3307	1.937	1.315	0.945	0.472	0.843	3.311	0.874	0.313	7/16-20	11798	8093	1.30	2.86									
2-7/16	212-39													110	49.2	33.4	24	12	21.4	84.1	22.2	8	1.09	2.41

Note: Add "G" suffix for relube type, (e.g., SA205-16G). Grease groove is on locking collar side of outer ring as standard and can be manufactured on the opposite side upon request.
Metric bore sizes also available upon request.