



Shaft Dia. in. d	SST Bearing No.	Dimensions (in.) (mm)								Load Rating lb.		Weight											
		D	Bi	Be	r	n	m	G	ds	Dynamic	Static	kg	lbs.										
1/2	SB201-8	1.5748	0.866	0.472	0.039	0.236	0.0630	0.177	#10-32	2750	1072	0.09	0.20										
5/8	202-10	40	22	12	1	6	16	4.5	*			0.08	0.18										
3/4	SB204-12	1.8504	0.984	0.551	0.059	0.275	0.708	0.177	#10-32	2880	1484	0.13	0.29										
		47	25	14	1.5	7	18	4.5	*														
1	CSB105-16	1.8504	0.984	0.9650	0.059	0.236	0.729	0.218	#10-32	1744	1159	0.16	0.35										
		47	25	24.5	1.5	6	18.50	5.53	*														
7/8	SB205-14	2.0472	1.062	0.591	0.059	0.295	0.767	0.217	#10-32	3152	1765	0.18	0.40										
15/16	205-15													52	27	15	1.5	7.5	19.5	5.5	*		
1	205-16																					0.17	0.37
1-1/16	SB206-17	2.4409	1.181	0.630	0.059	0.315	0.866	0.217	1/4-28	4375	2542	0.28	0.62										
1-1/8	206-18													62	30	16	1.5	8	22	5.5	**		
1-3/16	206-19																					0.26	0.57
1-1/4	206-20																					0.25	0.55
1-1/4	SB207-20	2.8346	1.259	0.669	0.079	0.335	0.925	0.256	1/4-28	5777	3459	0.43	0.95										
1-5/16	207-21													72	32	17	2	8.5	23.5	6.5	**		
1-3/8	207-22																					0.41	0.90
1-7/16	207-23																					0.38	0.84
1-1/2	SB208-24	3.1496	1.338	0.708	0.079	0.354	0.984	0.276	5/16-24	5787	4042	0.60	1.32										
1-9/16	208-25													80	34	18	2	9	25	7	0.58	1.28	
1-5/8	SB209-26	3.3465	1.621	0.748	0.079	0.402	1.219	0.322	5/16-24	7357	4598	0.8	1.8										
1-11/16	209-27													85	41.2	19	2	10.2	31	8.2			
1-3/4	209-28																						
1-7/8	SB210-30	3.5433	1.714	0.787	0.079	0.430	1.284	0.362	5/16-24	7895	5180	0.8	1.8										
1-15/16	210-31													90	43.5	20	2	10.9	32.6	9.2			
2	SB211-32	3.9370	1.783	0.826	0.098	0.466	1.317	0.385	5/16-24	9757	6552	1.1	2.4										
2-3/16	211-35													100	45.3	21	2.5	11.8	33.5	9.8	9752	6601	
2-1/4	SB212-36	4.3307	2.114	0.866	0.098	0.586	1.248	0.385	3/8-24	11789	8093	1.3	2.9										
2-7/16	212-39													110	53.7	22	2.5	14.9	31.7	9.8			

Note: Add "G" suffix for relube type, (e.g., SB205-16G). Grease groove is on set screw side of outer ring as standard and can be manufactured on the opposite side upon request.

*1/4-28 set screws can be furnished upon request.

**5/16-24 set screws can be furnished upon request.

Metric bore sizes available upon request.